

HAUG



Sauer Compressors



Oil-free piston compressor

- 4 – 11 kW
- Suction pressure atmospheric
- Final pressure max. 60 barg
- Max. 45 Nm³/h
- Air-cooled

HAUG.Taurus

Dependable up to 500 bar – anywhere, anytime, anygas.

Headquarters Switzerland:

HAUG Sauer Kompressoren AG
Industriestrasse 6
CH-9015 St. Gallen
Tel. +41 71 313 99 55
Fax +41 71 313 99 50
info@haug.ch
www.haug.ch

Branch office Germany:

HAUG Kompressoren GmbH
Altenhasslauer Str. 23
DE-63589 Linsengericht
Tel. +49 6051 97570
Fax +49 6051 975729
info@haug.ch

Branch office China:

HAUG China
No. 526, 3rd East Fute Road
Pilot Free Trade Zone
200131 Shanghai, China
Tel. +8621 5442 4551
sales-china@haug.ch

HAUG Sauer is a part of the world-
wide Sauer Compressors Group
www.sauercompressors.com

HAUG.Taurus – Oil-free piston compressor for air compression Power range 4.0 – 11 kW

The HAUG.Taurus series has been introduced to the market in 1994. Through splitting the crankshaft the HAUG.Taurus compressors can be constructed in a highly modular fashion. This is an advantage which is strongly appreciated by many customers and service technicians.

The oil-free compressors from the HAUG.Taurus series operate completely dry, i.e., without lubrication of the cylinder and without an oil bath in the crankcase. This prevents any contamination of the compressed air by lubricating oil.

The HAUG.Taurus compressor is available in an air-cooled version. The modular HAUG.Taurus compressor concept allows highly individual and cost-effective adaptation of the compressor configuration to the customer's requirements. This allows development of technically, commercially and energetically optimised solutions.

HAUG.Taurus compressors can be installed universally. They are suitable for continuous operation, intermittent operation or emergency operation with long downtimes. These dry-running compressors are very reliable and enable economic operation without idling costs.

Features

- Complete oil-free and dry-running piston compressor for air compression
- Air-cooled
- Motor power from 4 to 11 kW
- Rotary speed range 970 to 1450 1/min
- Suction pressure is atmospheric
- Final discharge pressure max. approx. 16 bar with 2-stage versions
- Final discharge pressure max. approx. 60 bar with 3-stage versions
- Modular cylinder configurations with cylinder diameter up to 100 mm
- Versions with 2 or 3 cylinders with 1-, 2- or 3-stage compression
- Maximum flow rate at atmospheric intake pressure approx. 48 m³/h
- Explosion-proof compressor version (conform with ATEX zone 1 or zone 2)
- Very robust and long-lasting construction
- Compact, space-saving and foundation-free installation
- Options with integrated control unit and noise-proof cover

Applications

- Pneumatic control
- Water and energy supply
- Chemical industry
- Pharmaceutical industry
- Medical compressed air
- Foodstuff and beverage industry
- Electronic industry
- Textile industry